

Features

- 4-line alphanumeric display, (20 characters per line)
- Up to 40 inbox message slots
- Up to 24 info slots
- Time and date display
- Time and date stamping
- Unread message reminder alert
- Protect up to 20 inbox, 20 saved messages
- 5 history records in info
- Info alert - individual slot control
- Battery level indicator
- Out-of-range indicator
- Continuous message indicator
- EL back light
- Memory retention
- 1 daily alarm
- Vibrate/ 8 pleasing/ vibrate then audible/ no alert
- 3-speed page scrolling
- Zoom in from 4-line to 2-line display
- Adjustable LCD contrast (0-7 level)
- Low cell reminder
- Priority call
- 4 selectable alert durations; 8sec/16sec/40sec/continuous (PPS option)
- 3 selectable alert modes; All alert, audio only, vibrate/sleep (PPS option)
- Tone message (PPS option)
- PPS programmable group and folders name

Synthesized POCSAG 4-line Alphanumeric Pager



Specifications

| | | | |
|-------------------------|---|-------------|---------------|
| Model no. | Br802 | | |
| Frequency: | VHF (135 - 175MHz), UHF (452 - 468MHz), 900MHz (929-932MHz) | | |
| Code Format: | 31/21 POCSAG Code | | |
| Channel Spacing: | 12.5 kHz, 25 kHz | | |
| Frequency Deviation: | +/- 4.5 kHz | | |
| Paging Sensitivity: | VHF/UHF | 900MHz | (c.f. 22.5dB) |
| EIA Selectivity: | 55 dB | 40 dB | |
| EIA Spurious and Image: | 50 dB | 40 dB | |
| IM Rejection: | 50 dB | 40 dB | |
| Operating Temperature: | -10°C to 50°C | 5°C to 40°C | |
| Alert Tone Loudness: | 75 dB @ 12 inches | | |
| Battery Type: | 1 x Alkaline AA | | |
| Weight (with battery): | 65 grams | | |
| Dimensions: | 80 x 54 x 19 mm | | |



RAD DEV FOR HAZ LOC INT SAFE
CI.I,Div1,Gr.CD, CI.I,Div2,Gr.ABCD, Exia, T4