



noise-com® unit boom microphone

The SAVOX noise-com® is a smart, flexible and cost effective handsfree communication solution for high-noise environments. The SAVOX noise-com® increases both personal safety and work efficiency. It fits in almost any muff type of hearing protectors, turning them into a professional communication headset. Still it maintains the function of the hearing protector. The SAVOX noise-com® is light weight, durable and ideal for industrial and utility personnel, airline ground crews, public safety applications - wherever hearing protectors are used.

The intrinsically safe SAVOX noise-com® connects directly or through a SAVOX® com-control/PTT unit to most types of two-way radios /phones.
The SAVOX® NC is ATEX Approved.

noise-com® unit boom microphone



Specifications

Weight	81g
Size	70 x 175 mm
Mic supply voltage	2.5...10,0 VDC
Directivity	noise cancelling
Mic impedance	2500 ohm @1 kHz
Speaker impedance	360 ohm @1kHz (±15%)
Cable	coiled: Ø 4mm /270mm, PUR, flame retardant (SAVOX® NC Direct: according to radio/phone)
Connector	4-pole, quick release plug (SAVOX® NC Direct: according to radio/phone)
Operation temperature	-25...+63 °C, (continuous)
Supply voltage	2,5...10,0 VDC
Humidity	95%RH,+63 °C for 500 hours
ESD,EMI immunity	confirms with the EN 301 489-1
Comaptibility	all SAVOX® com-control/push-to-talk units
Options	SAVOXNC compatible with all SAVOX® com-control/push-to-talk units, ATEX Approved SAVOXNC Direct with radio/phone specific adaptor cable, integrated PTT

